

4 Port Rail Manifold

**Centralises supply and distributes
to four different outlet feeds**

Overview

Speedfit 4 port rail manifold is a plastic push-fit manifold for centralising water distribution. The manifold allows for a main supply feed to be split into four reduced outlet feeds. Simply push the pipe fully onto the fitting. To demount the connection, push the collet towards the body of the fitting and pull the pipe to release.

The fitting is quicker and easier to install in confined spaces than traditional methods as it eliminates the need for hot works or tools in the loft environment.

Designed, manufactured and assembled in the UK.



Features & Benefits

- Instant push-fit connection
- Install and demount in seconds without tools
- Safe flame-free installation, with no hot works, glue or flux
- Grip & Seal collet with stainless steel teeth and main O-Ring seal
- Non-toxic, resists corrosion and no scale build-up
- Suitable for use with JG Speedfit PEX and polybutylene barrier pipe (inserts required) and copper pipe
- Suitable for hot, cold and central heating applications

Product code	Description	Size	Bag QTY
SFM522210	Rail Manifold	22 x 10mm	5
SFM522215	Rail Manifold	22 x 15mm	5



50 year guarantee when used with
JG Speedfit Layflat PB and PEX
Barrier Pipes

4 Port Rail Manifold

Working parameters & specifications

Application	Usual working temperature °C	Maximum working temperature °C	Maximum working pressure, bar
Cold Water (indirect and direct mains)	20	20	12
Central Heating	82	92	3
Hot Water (including unvented cylinders)	65	95	6

Mat

Body	Polyphenylene Sulphide (Glass Filled), Black
O-Ring	Ethylene Polypropylene Diene Monomer (EPDM)
Collet	Acetal Copolymer Black, Stainless Steel
Cartridges	Acetal Copolymer Grey, Stainless Steel
Support Washers	Acetal Copolymer Light Grey, Stainless Steel

Dimensions – All measurements in mm unless stated

