

Stop Tap MDPE x Copper, PEX or PB

Quick to connect screw down type, MDPE to copper, PEX or PB pipe mains stop valve

Overview

Speedfit push-fit MDPE to Copper, PEX or PB screw down mains valve instantly shuts off water. Simply push the valve fully onto the pipe. To demount, pull the collet towards the body of the fitting and pull the pipe to release.

Simply push the fitting fully onto the pipe. The connection is demountable, making it easy to work with in the ground when maintaining or altering an existing set-up.

Designed, manufactured and assembled in the UK.

Features & Benefits

- Instant push-fit connection and screw down mains stop valve
- Install and demount in seconds without tools
- Stainless steel teeth grab ring provides extra grip on the pipe
- Durable material with high impact resistance
- Non-toxic and no scale build-up
- Resists corrosion and biological growth
- Compatible with MDPE pipes only (inserts required)
- Suitable for cold water use only



Product code	Description	Size	Bag QTY
UGSTV2515	Stop Tap MDPE x Copper, PEX or PB	25 x 15mm	1
UGSTV2522	Stop Tap MDPE x Copper, PEX or PB	25 x 22mm	1



Working parameters & specifications

Materials	
Body	Polypropylene (Glass Filled), Black
O-Ring	Ethylene Polypropylene Diene Monomer (EPDM)
Collet	Acetal Copolymer (Unfilled) Blue
Collet Teeth	Stainless Steel
Collet Cover	Acetal Copolymer (Unfilled) Blue
Support Washer	Acetal Copolymer (Unfilled) Blue
Spindle	Nylon 66 (Mineral Filled), Natural
Top Cover	Acetal Copolymer (Unfilled) Black
Locking Ring	Acetal Copolymer (Unfilled) Mid Blue

Technical drawing of the UG5T2515 valve assembly. The drawing shows a side view of the valve with a blue handle on top and a blue actuator on the right. Dimensions are provided in millimeters (mm).

Dimensions:

- Top handle width: $\varnothing 90.6$
- Overall height: 113.5
- Actuator length: 66.0
- Tube insertion depth (actuator): 88.3
- Tube insertion depth (valve body): 29.0
- Overall width: 52.8
- Min Thro' Bore: $\varnothing 13.2$
- Thro' Bore: $\varnothing 19.0$
- Tube Detail dimensions: $+0.05$, $\varnothing 15.0$, -0.10
- Tube Detail dimensions: $+0.3$, $\varnothing 25.0$, 0.0

Labels:

- *With Collet In Release Position
- UG5T2515

